



-3 REINFORCEMENT

-2 FIREWALL

QTY	NO. REQ.	SIZE	DESCRIPTION
8		3/32 x 7/64	STEEL TUBULAR CADPLATED RIVET
-3	4	.0156 x 1 1/2 x 3	TYPE #430 ST STEEL ANNEALED 2D-FIN.
		.018 x 1 1/2 x 3	ALUM NIZED H.R. STEEL
-2	1	.0156 x 26 x 29 15/16	TYPE #130 ST. STEEL ANNEALED 2D-FIN. CR.
		.018 x 26 x 29 15/16	ALUMINIZED H.R. STEEL

PART NO. _____
 SCALE 2 IN. = 1 FT. & NOTED TOTAL WT.-LBS.
 FINISH-PIPER SPECIFICATION #10
 MANUFACTURING PRACTICES-PIPER SPECIFICATION #9

FIREWALL ASSEMBLY

REVISION	DATE	BY
L	4-15-47	C.E.K.
K	1-29-47	C.E.K.
J	1-20-47	M.P.Z.
H	1-20-47	M.P.Z.
G	12-20-46	M.P.M.
F	11-21-46	M.P.M.
E	11-21-46	M.P.M.
D	10-18-46	C.E.K.
C	9-16-46	J.D.
B	8-7-46	M.P.Z.
A	8-23-46	J.H.

LET. _____ DATE BY _____

THIS DRAWING IS THE PROPERTY OF THE PIPER AIRCRAFT CORP. AND ITS POSSESSION BY UNAUTHORIZED PERSONS SHALL NOT BE CONSIDERED AS PERMISSION TO REPRODUCE FOR SALE, IN WHOLE OR IN PART, ANY DEVICES SHOWN THEREON.

MODEL PER PLANE NEXT ASSEMBLY SUPERSEDES SUP. BY

PIPER AIRCRAFT CORP.
 LOCK HAVEN, PENNA.

C.E.K. 2-17-46
 DRAFTSMAN
 P.E.T. 2-26-46
 CHECKER
 STANDARDS

10792

A714